



PORTABLE T-SORT POWERED BELT CONVEYOR

POWERED REVERSIBLE BELT CONVEYOR IDEAL FOR FULL RANGE OF SIZES & WEIGHTS

DETAILS

Belt Width: 35.5"

Length without chute: 192"

Length with chute: 288.25"

Motor: 1 HP

Speed: 60 fpm

- Reversible Direction
- Variable Speed

IDEAL END USES

Our Mobile Powered Belt Conveyor technology can be applied throughout your operation in a variety of ways:

- Manual Sort Operations
- Loading & unloading Transport Vehicles

INDUSTRY NEED

Often, Distribution and Sort facilities require special help handling oversize, or heavy packages. Sometimes these packages cannot travel certain areas of the conveyor system and need to be loaded or off loaded in different areas of the facilities. From time to time, creative methods for loading or unloading trailers or vans are required as well.

OUR SOLUTION

We developed a **Portable T-Sort Powered Belt Conveyor** with a mating portable gravity section designed for mobility. This heavy duty unit is remarkable easy to move, and offers a simple and effective means to handle difficult to convey products in sorting, loading, or unloading applications. The UHMW lined Chute provides a low friction surface at interface points, allowing operators to easily transfer these challenging items on or off the adjoining surfaces. The unit is driven with a 2 HP reversible motorized pulley that uses 115V, 1ph power. Its 20 ft long power cord is supplied with a twist lock plug that stays put. This conveyor is a multi-use unit that is easily deployed for whatever your special use needs might be.

FEATURES & BENEFITS

- 8" Offset Heavy Duty Swivel locking casters allow for **easy maneuvering**
- Reversible incline/decline
- Lift Gate for **egress access**
- 115 V Single phase power
- **Removable side rails** for oversized packages
- Optional gravity roller in-feed conveyor
- Plug & Play Electrical connections
- Variable Speed

PORTABLE T-SORT POWERED BELT CONVEYOR

POWERED REVERSIBLE BELT CONVEYOR IDEAL FOR FULL RANGE OF SIZES & WEIGHTS

SPECIFICATIONS

STANDARD FEATURES

- **Elevation:** 31" infeed and 54" discharge
- Heavy-duty Leg supports with swivel caster and wheel lock
- Removable guardrail

TECHNICAL DATA

WARRANTY

- Mechanical: **12 Months**

SERVICES AVAILABLE

- Technical Support
- Installation & Setup
- Service Maintenance
- Application Support
- Hardware Support



SHOWN WITH
PIVOTING CHUTE EXTENDED