

PARCEL BELT CHUTES



CONCAVE TIP



SPIRAL



SPIRAL TIP

DETAILS

WIDTHS: Custom

ELEVATIONS: Custom

SIDE GUARD: Custom

MATERIAL: 12ga Galvanized with optional UHMW Liner.

SUPPORTS: Structural Tube Supports

COUNTERWEIGHT: Manual with locking

OPTIONAL: Chute Extension

STANDARD WIDTHS: 36" / 42" / 48" / 60"

INNER RADIUS: 30" - 36"

IN-FEED-DISCHARGE: 29.5" / 40.5a"

STANDARD ANGLES: 45° / 60° / 90°

MATERIAL: 12ga Galvanized with optional UHMW Liner.

SUPPORTS: Optional supports can be added if free standing.

OPTIONAL: Chute Extension

STANDARD WIDTHS: 36" / 42" / 48" / 60"

TAPERED WIDTHS -

- 60" infeed tapered down to 48" discharge
- 78" infeed tapered down to

ELEVATIONS: Custom

SPIRAL ANGLES: 45° / 60° / 90°

MATERIAL: 12ga Galvanized with optional UHMW Liner.

SUPPORTS: Structural Tube Supports

COUNTERWEIGHT: Manual with locking

OPTIONAL: Chute Extension

APPLICATION SPECIFIC

These are just a few of our Chute options that we offer. No two system solutions are exactly alike, which means many Chute solutions are application specific.